

S29 Waterproof Bench Scales

General Specifications

- Display 25mm digit LCD display, with white LED backlight
- Capacities 3kg~25kg
- Platform size 230 x 190mm
- Keyboard 3 keys (Mechanical switch)
- Housing Stainless steel
- Max. Divisions 3,000e; 2 x 3,000e; 6,000d
- ADC update $\leq 1/10$ second
- Operating Temp. $-10^{\circ}\text{C} \sim +40^{\circ}\text{C}$
- Power AC adapter (12V/500mA), internal rechargeable battery (6V/3.2Ah)
- Gross weight 4.2kg
- Packing Master carton 4 in 1, dimension 0.115m^3



- IP65 waterproof technology patented in China
- Selectable weighing units
- Hand operated pressure equalisation valve
- OIML approval from DELTA (approval no. DK0199.255)
- Battery provides up to 70 hours of continuous use (without backlight)
- Optional 20mm rear display
- Optional initial-verification



S29 Waterproof Bench Scales

Model Name	Capacity	Readability	Division	Approx. weight	Approval
S29-3K	3kg	0.5g	6,000d	4.2kg	CE
S29-6K	6kg	1g	6,000d	4.2kg	CE
S29-15K	15kg	2g	6,000d	4.2kg	CE
S29-25K	25kg	5g	6,000d	4.2kg	CE
S29-3K-M	3kg	1g	3,000e	4.2kg	CE, OIML
S29-6K-M	6kg	2g	3,000e	4.2kg	CE, OIML
S29-15K-M	15kg	5g	3,000e	4.2kg	CE, OIML
S29-25K-M	25kg	10g	3,000e	4.2kg	CE, OIML
S29-6K-MR	6kg	1g/2g	2 x 3,000e	4.2kg	CE, OIML
S29-15K-MR	15kg	2g/5g	2 x 3,000e	4.2kg	CE, OIML
S29-25K-MR	25kg	5g/10g	2 x 3,000e	4.2kg	CE, OIML

Options



Dimensions(mm)

